

**NEW
SERIES!**

TR AND SR SERIES



TR and SR Series - Features:

- Triplex plunger pump
- Up to 236 GPM and 22,000 PSI
- 300 HP or 450 HP
- Can be mounted vertically or horizontally
- Double end crankshaft
- Internal gear reduction
- Forced oil lubrication with integrated cooler, filter and gauge
- Solid ceramic plungers
- Available in three gear ratios (520 internal RPM):
1500 RPM=2.90:1, 1800 RPM=3.46:1,
2200 RPM=4.23:1

TR and SR Series - Specifications:

Inlet Pressure.....	30-70 PSI
Shaft Diameter.....	2.56"/65 mm
TR Stroke.....	5.12"/130 mm
SR Stroke.....	3.54"/90 mm
Pump Dimensions.....	50.0"x41.0"x28.5"
Crankcase Oil Capacity.....	9.24 gal. (vertical) 13.75 gal. (horizontal)
	Use GP Series 220 Oil (see page 55)
Shipping Weight	2,436 lbs.
Product Group	V

TR and SR Series - Materials:

- Cast iron crankcase
- Stainless steel manifold
- Steel alloy crankshaft
- Forged steel connecting rods and connecting bushings

TR SERIES			
MODEL	GPM	PSI	RPM
TR26	28.5 GPM	21,755 PSI	520 RPM
TR30	37.8 GPM	17,404 PSI	520 RPM
TR36	55.0 GPM	10,877 PSI	520 RPM
TR50	105.0 GPM	5,801 PSI	520 RPM
TR60	157.4 GPM	4,351 PSI	520 RPM
TR70	206.0 GPM	3,190 PSI	520 RPM
TR75	236.0 GPM	2,755 PSI	520 RPM

SR SERIES			
MODEL	GPM	PSI	RPM
SR26	19.8 GPM	21,755 PSI	520 RPM
SR30	26.0 GPM	17,404 PSI	520 RPM
SR32	29.8 GPM	14,503 PSI	520 RPM
SR36	37.8 GPM	11,603 PSI	520 RPM
SR50	73.0 GPM	5,801 PSI	520 RPM
SR65	123.0 GPM	3,425 PSI	520 RPM
SR75	163.7 GPM	2,755 PSI	520 RPM

**CONTACT YOUR GENERAL PUMP
SALES REPRESENTATIVE FOR
FURTHER DETAILS**