

Industrial Pump Oil

Series 220



- General Pump Industrial Oil is a premium multipurpose lubricant formulated to protect against rust and oxidation. It offers long service life and prevents sludge and varnish formation - even at high temperatures.
- General Pump Industrial Oil possesses a high natural viscosity index. This means more constant operating characteristics over a wide temperature range.
- Recommended for use in General Pump Industrial Pump crankcases. Initial oil change after break-in period between 50 and 100 hours. then every 3 months or 500 hours of operation thereafter. Check oil level in crankcase daily or before each use.
- Regular lubrication is the easiest, most efficient and least expensive element in preventive maintenance.

100217 5 gallon twin pack (Two 2-1/2 gallon bottles)

FEATURES/BENEFITS

- Special anti-scuff and anti-wear agents extend the lives of gear, vane, radial piston and plunger pumps.
- Resists foaming and aeration which would result in erratic equipment operation and increased oil oxidation.
- Highly resistant to oxidation that would result in sludge formation.
- Resists formation of harmful oil water emulsions.
- Compatible with typically used seals and gaskets.
- High viscosity index (VI) means more constant operating characteristics over wide temperature ranges.
- Low pour point assures fluid flow during cold weather operation.
- Outstanding thermal and hydrolytic stability assures long oil life.
- Exceeds wear prevention requirements of all major hydraulic pump manufacturers.



General Pump
is a member of
the Interpump Group

Ref 300034 Rev C
07-09



GENERAL PUMP • 1174 Northland Drive • Mendota Heights, MN 55120
Phone: (651)686-2199 • Fax: (800)535-1745 • email: sales@gpcompanies.com • www.generalpump.com