Accessories

New higher flow industrial flow switch, in brass.

100918 - Flow Switch



100919 - Flow Switch New higher flow industrial flow switch, in stainless steel.



ZK3608SS - Trapped **Pressure Unloader** 3600 PSI stainless steel.



ZK5810 - Trapped Pressure Unloader 2.11 - 11.06 GPM 5800 PSI.



ZK1 - Unloader 3600 PSI Available with 3/8" outlet.



100869C-100870C

Waterbroom Assemblies Available in 12" and 16".

100874-Injector **Stainless Steel Chemical** Injectors.



100906 - Chemical **Pulse Pump** Perfect for carpet cleaning.



YG5000C - Popular YG5000 spray gun With ceramic ball for chlorine applications.





DLTG12/DLTG18/DLTG24 Telescoping wands available in 12', 18', and 24' sizes.



D30006 Expanded hose reel line now available in 50', 100' and 200' sizes ..




GP Companies, Inc. **1174 Northland Drive** Mendota Heights, MN 55120

888.474.5487 www.generalpump.com email: sales@gpcompanies.com



YGR1000P - Gearbox, 24 HP, 1" Improved, higher HP gear boxes for more industrial applications.



We Call It Home.

Now your equipment will work in the toughest of environments with the Emperor line of pumps with HT technology. The Emperor line features "High Tech" packing and "High Temp" valve design. These premium pumps can withstand temperatures up to 185^o F and can run dry for several hours. The nickel-plated manifold and valve plugs provide corrosion-resistant operation and help reduce damage caused by cavitation. Choose from a variety of different size pumps for a variety of applications where hot water is required.



HTC Series

HTC Series (60HT) - Ideal for use in carpet cleaning and other high pressure cleaning applications where hot water is required. This pump offers a compact, economical design. GPM PSI RPM Model Number HTC1505E345 3400 2.1 2200 HTC1509E175 2.1 2200 1750

Pumps That Rule Any Environment

The Emperor Line Of Pumps With HT Technology

HTW Series

HTW Series (69HT) - Designed for touchless carwash systems, multiple gun systems and industrial plant systems where hot water is required.I Model Number RPM GPM PSI HTW3624 1000 18.0 1200



HTS Series

HTS Series (47HT) - Specifically designed to handle the rigorous duty cycles, high temperatures and chemicals associated with self-service car wash applications. Also ideal for use in carpet cleaning and other high pressure cleaning applications.

ereaning appreaderer						
Model Number	RPM	GPM	PSI			
HTS2210S	950/1450	2.6/4.0	2300			
HTS2212S	950/1450	3.2/4.75	2300			
HTS2215S*	950/1200	4.0/5.0	2300			
*Same RPM and Flow as Cat 310/5CP2120						



Series

HTF Series (66HT) - Designed for use in prep units, conveyor and multiple gun applications. Excellent for carpet cleaning and for use in industrial plant systems where hot water is required.

Model Number	RPM	GPM	PSI
HTF2018S	950/1200/1750	4.0/5.0/7.5	3600
HTF2221S	1450/1750	8.510.2	3000
HTF2421S	1450/1750	10.0/12.0	3000/
			2500



Series

Mode

HTX1

HTX1

HTX1

HTX Series (63HT) - Specifically designed to handle the rigorous duty cycles, high temperatures and chemicals associated with self-service car wash applications. Also ideal for use in carpet cleaning and other high pressure cleaning applications. This pump offers a compact, economical design.

pump offers	a compact,	economical	aesign
l Number	RPM	GPM	PSI
1810S	1450/1750	2.7/3.1	2000
1812S	1450/1750	3.2/3.8	2000
1813S	1450	3.5	2500



HTCK3623S HTCK3623S Series (70HT) - Ideal specifically for

use in rollover car wash systems and other industrial plant systems where hot water is required.

Aodel Number	RPM	GPM	
ITCK3623S	1150	21	



HTCK4050S HTCK4050S Series (71HT) - Designed as a direct

HICK4050S Series (71H1) - Designed as a directreplacement for Cat's 3535 with the distinctadvantage of featuring General Pump's patentedHT technology. Ideal for use in rollover carwashes and other industrial applications wherehot water is required.Model NumberRPMGPMHTCK4050S800361500

To find out more about the complete line of Emperor pumps contact General Pump today.



888.474.5487 www.generalpump.com

M Nick

The Emperor Line of Pumps With HT Technology Provides:

High Temperature/Run Dry Seal Capability

- (Patent Pending)
 - dynamic low-pressure seal retainer
 - aligns to crankcase
 - taper area reduces friction between retainer
 - ceramic plunger and allows for better drainage

superior low-pressure seal - proprietary compound of teflon (PTFE) and graphite - stainless steel spring energized

- u-seal

innovative intermediate ring - raised area fills some of the space of the low-pressure seal, which helps it

energize faster in suction conditions

superior high pressure seal - proprietary compound of teflon (PTFE) and graphite - stainless steel spring energized - seal

Inlet/Outlet Valve Seal (Patent Pending)

- teflon bronze support
- special o-ring
- o-ring shape on inside and
- outside diameter to make installation easier
- flat surface on top and bottom
- NBR90

Inlet/Outlet Valve Cage (Patent Pending) • 6 post design - stronger

new "high temp" plastic

Nickel-Plated Inlet/Outlet Valve Plugs offers better corrosion protection

twice as thick as competitors harder



