Pumps Made Ready

BY GENERAL PUMP

PMREZ4040G

- 1" Hollow shaft with gas flange
- · Quick coupler and plug included
- Maximum Flow: 4 GPM
- 4.000 PSI at 3.400 RPM



PMRTSS1511

- 24 mm solid shaft
- Quick coupler and plug included
- Maximum Flow: 4 GPM
- 3,500 PSI at 1,450 RPM

PMRET1507G6

- 3/4" Hollow shaft with gas flange
- Quick coupler and plug included
- Maximum Flow: 3.3 GPM
- 2.610 PSI at 3.400 RPM

PMRET1506G6

- 3/4" Hollow shaft with gas flange
- Quick coupler and plug included
- Maximum Flow: 2.9 GPM
- 2.610 PSI at 3.400 RPM



PMRES2012S

- · 24 mm Solid shaft
- Quick coupler and plug included
- Maximum Flow: 4.76 GPM
- 4,000 PSI at 1,750 RPM

PMREP1313G8

- 1" Hollow shaft with gas flange
- · Quick coupler and plug included
- Maximum Flow: 4 GPM
- 4,000 PSI at 3,400 RPM

PMREP1508G8

- 1" Hollow shaft with gas flange
- Quick coupler and plug included
- Maximum Flow: 3.4 GPM
- 3,045 PSI at 3,400 RPM



General Pump is a member of The Interpump Group



Pumps Made Ready BY GENERAL PUMP

PMREP1812E17

- 1 1/8" Hollow shaft with electric flange NEMA184TC
- Quick coupler and plug included
- Maximum Flow: 4 GPM
- 2,500 PSI at 1,750 RPM



PMRTS2021

- 24 mm Solid shaft
- Quick coupler and plug included
- Maximum Flow: 5.6 GPM
- 3,500 PSI at 1,450 RPM

PMRTSF2021

- 24 mm Solid shaft
- Quick coupler and plug included
- Maximum Flow: 8.5 GPM
- 3,600 PSI at 1,750 RPM

PMRTSF2221

- 24 mm Solid shaft
- Quick coupler and plug included
- Maximum Flow: 10.2 GPM
- 3,000 PSI at 1,750 RPM





PMRET1505E34

- 5/8" Hollow shaft with electric flange NEMA56C
- Quick coupler and plug included
- Maximum Flow: 2.1 GPM
- 2,610 PSI at 3,400 RPM
- · Hot kit optional

GENERAL PUMP

1174 Northland Drive Mendota Heights, MN 55120

Phone: 651.686.2199 FAX: 800.535.1745 e-mail: sales@gpcompanies.com www.generalpump.com facebook.com/gpcompanies www.youtube.com/user/GeneralPump

PMRET1509E17

- 5/8" Hollow shaft with electric flange NEMA56C
- Quick coupler and plug included
- Maximum Flow: 2.1 GPM
- 2,610 PSI at 1,700 RPM
- Hot kit optional

PMRET1809E17

- 5/8" Hollow shaft with electric flange NEMA56C
- Quick coupler and plug included
- Maximum Flow: 3.2 GPM
- 2,320 PSI at 1,700 RPM

PMRET1506E34

- 5/8" Hollow shaft with electric flange NEMA56C
- Quick coupler and plug included
- Maximum Flow: 2.9 GPM
- 2,610 PSI at 3,400 RPM Hot kit optional
- Rev. B 08-19 GENERAL PUMP